




SILVER 250 Series

SILVER 252iX





SILVER LINE - SILVER 250 Series

SILVER 252iX

Optical system	Infinity optical system
Observation tube	Binocular head, Siedentopf type with Built-in digital Wi-Fi camera
Sensor type	CMOS
Sensor size	1/3"
Capture resolution	4MP (2592x1520 pixels)
Live display mode through Wi-Fi	1280x720, 1920x1080 pixels (Full HD)
Live display mode through ethernet	1280x720, 1920x1080 pixels (Full HD)
Data transfer	Wi-Fi (2.4 & 5 GHz), Ethernet
Inclination	30° inclined
Interpupillary distance	55-75mm
Diopter adjustment	On left tube, +/- 5 diopter
Eyepieces	Widefield WF10X/20mm
Nosepiece	Reversed quadruple
Objective classification	Infinity Plan Achromatic, DIN
Objectives	4X/0.10, 10X/0.25, 40X/0.65/S, 100X/1.25/S-Oil
Objective mounting thread	W 4/5"x1/36" (RMS standard)
Stand type	Upright
Stage	Mechanical stage with built-in low position coaxial stage control and sample holder
Stage size	140x140mm
Travel range X&Y	77x50mm
Condenser	Focusable Abbe condenser N.A. 1.25 with slot for contrast sliders
Diaphragm	Iris diaphragm
Focus mechanism	Coaxial coarse and fine focusing system with tension adjustment
Fine focus precision	2µm
Focusing stroke	22mm
Upper limit stop	Upper limit stop preset but adjustable
Filter	Built-in frosted glass
Transmitted illumination	LED 3W with intensity control
Software	Motic Images Plus 3.1 for Windows 10, MAC OSX10.9 or higher
Transformer	External
Power supply	100-240V (CE)
Accessories included	Dust cover, immersion oil (5ml), charger, calibration slide
Dimensions LxWxH	390x185x380mm
Net weight	6.3kg